

# PINTUPLAST™

## PINTUPLAST™

is a versatile, high-solids, 100% acrylic, flat finish paint, and is ideal for application over EIFS acrylic textured finish coatings.

## Recommended Use

PINTUPLAST is used as a surface primer for Corev exterior textured coatings. It is ideal over alkali surfaces such as concrete, cement plaster, masonry or EIFS basecoat.

## Coverage

800 to 1000 ft<sup>2</sup> per 5 gallon bucket. Substrate characteristics and application technique will affect coverage.

## Color

PINTUPLAST can be tinted to almost any color.

## Properties

### Drying Time

Initial set: 2 hrs. @ 70°F; 50%RH  
Cure Time: 24 hrs. @ 70°F; 50%RH

Packaging (5 gallon bucket)  
54 lbs. net  
56.8 lbs. gross

### Reduction

Use potable water. Do not exceed 10% by volume.

## Application

### Surface Preparation

Surfaces must be clean, dry and free of dust, grease or other materials that may affect bonding. Previously painted surfaces must be scraped to remove all loose paint.

### Mixing Instructions

Stir to a homogeneous consistency.

### Application Procedures

Can be applied with brush, roller or spray equipment

## Clean Up

Clean equipment with water while PINTUPLAST is still wet.

## Storage

Store PINTUPLAST in its original container at temperatures not less than 40°F or greater than 110°F. Store out of direct sunlight. Do not stack pails more than three high.

## Shelf Life

Approximately one year if stored properly.

## Warranty

PINTUPLAST is conditionally warranted for 5 years against delamination, color fading, and mildew growth. FOR COMPLETE INFORMATION, CONSULT COREV AMERICA, INC. LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

## Limitations

- o Do not mix with other products.
- o Surface air and substrate temperatures must be 40°F or higher during application and for a period of 24 hours thereafter.
- o PINTUPLAST is not compatible with solvent base products or cleaners.
- o Use in well ventilated areas. Protect all adjacent surfaces, door frames, windows, etc. Do not water down material. Prepare metal surfaces such as corner bead with rust inhibitors prior to PINTUPLAST application.
- o This product requires skilled application.
- o Use eye and face protection.
- o Avoid constant moisture in the wall cavity behind the coating.