

SOTTOFONDO™

SOTTOFONDO™

SOTTOFONDO is a clear, acrylic, permeable and mildew resistant primer sealer and bond enhancer.

Recommended Use

Exterior or interior primer sealer for sealing new or previously painted masonry and drywall surfaces. Adheres well to semi-gloss surfaces and acts as a bonding primer on substrates such as ceramic tile, glazed brick, and non-ferrous metal surfaces.

Coverage

Each 5 gallon bucket provides approximately 1,000 to 1,200 square feet of coverage over new drywall. Variations in surface porosity, ambient conditions and individual application technique will affect coverage.

Packaging

1 gal. bucket: 7 lbs. net; 7.5 lbs. gross
5 gal. bucket: 36 lbs. net; 38.8 lbs. gross

Properties

Drying Time

Initial set: Approximately 2 hours at 77°F at 50% humidity
Cure: Approximately 24 hours at 77°F at 50% humidity

VOC Compliance: SOTTOFONDO complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers.

Reduction

The material in the buckets is ready for use. Reduction is not required or recommended.

Equipment

May be applied by brush or roller. Spray application is not recommended.

Application

Surfaces must be clean, dry, and free of dirt, grease or loose material. Uniformly apply SOTTOFONDO using a brush or roller. Allow surface to dry at least 24 hours prior to application of topcoat or adhesion of other materials. Always prepare a mockup for demonstration of adhesion characteristics

Clean-Up

Clean with water while SOTTOFONDO is still wet.

Storage

Store SOTTOFONDO in its original containers at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store out of direct sunlight. Do not stack buckets more than 3 high.

Shelf Life

Approximately 1 year if properly stored.

Warranty

Corev America's America's SOTTOFONDO is conditionally warranted for 10 years against delamination and mildew growth. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose, are expressly disclaimed.

Limitations

Substrates must be sound, clean, and free of cavities, cracks, and irregularities. Surface, air and material temperatures should be minimum 40°F and maximum 100°F during application and for a period of 24 hours after installation. SOTTOFONDO is not compatible with solvent based products or cleaners. Use in well ventilated areas. Protect all adjacent surfaces (door frames, windows, etc.) adequately. Do not water down material. The minimum required slope of surfaces to receive application of SOTTOFONDO is 6" of rise in any 12" of horizontal projection. SOTTOFONDO shall not be applied to inclined areas defined as roof. Avoid breathing vapors and prolonged contact with the skin.

Safety

ALWAYS WEAR APPROPRIATE EYE AND SKIN PROTECTION WHEN USING THIS PRODUCT. HARMFUL IF SWALLOWED. BEFORE APPLYING THE PRODUCTS REFER TO THE COMPLETE LONG FORM SPECIFICATIONS OF THE COREV AMERICA PRECOR EIFS SYSTEM.

Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of COREV products and is presented in good faith. COREV assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.