

MATERIAL SAFETY DATA SHEET (MSDS)



Adhesives

Section 1- General

Trade Name(s):	Unibase, Unibond, Unibase-WP
Chemical Name:	N/A
Synonyms:	Synthetic Stucco; Adhesives
Formula:	N/A
Chemical Family:	Acrylic Paint

Section 2 - Ingredients

Component	CAS No.	%	TLV
Ethylene Glycol	107-21-1	<2	50
Petroleum Solvent	64742-94-5	<2	100

Section 3 - Physical Data

Boiling Point:	N/A
Specific Gravity:	1.70
Vapor Pressure (MM/HG):	N/A
Melting Point:	N/A
Vapor Density:	N/A
Evaporation Rate:	N/A
Solubility in Water (g/100 g H ₂ O):	26.00
Appearance:	Semi-liquid paste
Odor Characteristics:	Almost odorless

Section 4 - Fire and Explosion Hazard Data

Not a Fire or Explosion Hazard

Section 5 - Reactivity Data

Stability:	Generally Stable
Incompatibility:	None Expected
Conditions to Avoid:	None Expected
Hazardous Decomposition:	None Expected
Hazardous Polymerization:	Will Not Occur



Adhesives

Section 6 - Health Hazard Data

Routes of Entry	Effects of Acute Exposure
Eye Contact	Eye contact causes irritation and possible corneal injury.
Skin Contact:	Prolonged or repeated skin contact may cause reddening, swelling and possible skin damage.
Inhalation:	Inhalation of high concentrations causes irritation of the respiratory tract. Symptoms include headaches, dizziness, nausea and malaise.
Ingestion:	Ingestion may cause headache, dizziness, lack of coordination, nausea, vomiting, diarrhea, general weakness, possible liver and kidney damage.
Carcinogenicity:	NTP: No IARC: No OSHA: No
Chronic Health Hazards:	Refer to Effects of Acute Exposure (above)
Medical Conditions Generally Aggravated by Exposure:	May adversely affect existing medical conditions such as eye, skin, respiratory, liver and/or kidney ailments.
Emergency and First Aid Procedures: Eye and Skin Contact: Inhalation: Ingestion:	Immediately flush with plenty of water for at least fifteen (15) minutes. Call a physician. Move to area with fresh air. If swallowed induce vomiting immediately as directed by medical personnel.

Section 7 - Precautions For Safe Handling and Use

If material is released or spilled:	Contain spillage, scoop into container for disposal. Residues may be washed off with water.
Waste disposal method :	Follow appropriate federal, state and local regulations regarding proper waste disposal.
Handling and Storing:	Store containers stacked no more than three (3) high at room temperature and avoid direct sunlight. Keep containers closed and protect from freezing conditions.

Section 8 - Control Measures

Respiratory Protection:	N/A
Ventilation:	When working in enclosed areas open windows or allow for air circulation.
Protective Equipment:	None required.
Work/Hygiene Practices:	Avoid breathing vapors, contact with eyes or skin. Use with adequate ventilation.